Simple/Reliable/Green/Efficient



INLET WINDOW SYSTEM

The inlet window system regulates airflow and ventilation in poultry houses, ensuring a healthy indoor environment.

















Spring Inlet Window

- Opening Mechanism: Driven open, spring tension ensures automatic closure.
- Sealing: Ribbed groove structure provides excellent sealing performance.
- Features: Equipped with an adjustable deflector to ensure airflow is evenly distributed to the center of the house.

Category	parameters	
The material	PS	
The hole size	560mm (W) *270mm (H)	840mm(W)*270mm(H)
Area	0.11 m²	0.16m²



Arched Inlet Window

- Closing Mechanism: Driven close, gravity-operated automatic opening.
- Sealing Material: PU seals ensure airtight closure.
- Features: Adjustable deflector angles optimize airflow direction, preventing direct drafts on poultry.

Category	parameters	
The material	PP+PVC	
The hole size	800mm(W)*270mm(H)	1200mm(W)*270mm(H)
Area	0.16m²	0.24m²
N0. of pull arms	1	2



Sidewall Large Window System

- Closing Mechanism: Driven close, gravity-operated automatic opening.
- Sealing: High-performance rubber seals prevent cold air infiltration.
- Features: Equipped with deflectors to adjust airflow direction, ensuring comprehensive ventilation.

Category	parameters
The material	PS+PVC
The hole size	800mm(W)*500mm(H)
Area	0.26m²
N0. of pull arms	1



BIG HERDSMAN MACHINERY(JIAOZHOU) CO.,LTD



